



# ODX-115

## OUTDOOR DIRECT EXPANSION (ODX) UNIT

*The OptiCool ODX-115 unit pairs with a single OptiCool RPC-115 pump to create a high quality system that provides precision cooling in any mission critical infrastructure where Direct expansion (DX) cooling applications are required.*

The OptiCool ODX-115 unit manages the transfer of heat from the RPC-115 pump to the outdoors using R-410A refrigerant. The unit has variable capacity compressors, which allow for low and fluctuating heat loads. The ODX-115 unit is air-cooled condenser that can be roof or ground-mounted.

The ODX-115 unit is part of a system and requires other OptiCool products for effective heat transfer out of the room. Each ODX-115 unit also requires an OptiCool RPC-115 pump.








### Specifications

ODX POWER CONSUMPTION**	41 Kw
ODX WEIGHT	1,800 lb
ODX DIMENSIONS	45 in x 98 in x 100 in
COMPRESSORS (BLDC SCROLL)	2
AMBIENT OPERATING RANGE	-40°F TO 120°F
MINIMUM LOAD REQUIRED***	12 kW
ODX/RPC EQUIVALENT SUPPLY LENGTH (MAX)***	185 ft
SECONDARY CIRCUIT REFRIGERANT	R-410a
MCA	480 V, 3 Phase, 75 amp 208 V / 230 V, 3 Phase, 165 amp
MOPD	480 V, 3 Phase, 100 amp 208 V / 230 V, 3 Phase, 225 amp
CERTIFICATION	ISO 9001

\*\* 100% @ Rated Condition of 95°F

\*\*\* Minimum load may vary with line length and elevation

### Features

-  Assembled in the USA
-  Integrated communication with RPC for data monitoring
-  Aesthetic design and light-weight with compact outdoor footprint
-  Redundant capable with multiple compressors
-  Variable speed compressors for precise temperature control and minimal power consumption



[Opticooltech.com](http://Opticooltech.com)  
[Info@opticooltech.com](mailto:Info@opticooltech.com)

855 Publishers pkwy,  
Webster, NY 14580 USA

Sales 585-347-6142  
Service 585-967-5434