



RPW-060

CHILLED WATER EXTERNAL HEAT REJECTION

The OptiCool RPW-060 system provides best-in-class precision cooling in any mission-critical infrastructure where chilled water is available.

The OptiCool RPW-060 is a highly efficient low-pressure pumped R-513A refrigerant system supporting up to 40 Active Heat eXtractor (AHX) units for applications achieving 60 kW of non-condensing 100% sensible cooling. Employing a pumped R-513A solution ensures a highly reliable, oil-free, nontoxic, non-conductive, and non-corrosive sustainable cooling ecosystem to efficiently extract heat at the source.

The RPW-060 pump is part of a system and requires other OptiCool products for effective heat transfer out of the room.

The RPW-060 system uses a chilled water system for external heat rejection. This chilled water system is typically existing facility infrastructure with sufficient capacity to handle the additional load from the RPW-060 system. Alternatively, a new chilled water package may be provided by a third party.



Specifications

MIN/MAX kW CAPACITY:	5 kW / 60 kW
EXTERNAL HEAT REJECTION:	CHILLED WATER or GLYCOL MIX
NUMBER OF AHX SUPPORTED:	3 to 40 per pump
POWER OPTIONS:	480 V, 3 Phase, 60 Hz 208 V / 230 V, 1 Phase, 60 Hz
FULL LOAD AMPS:	480 V, 6.5 amp 208 V / 230 V, 16 amp
PUMP DRY WEIGHT:	1,300 lb
PUMP DIMENSIONS:	30 in. x 82 in. x 40 in.
REFRIGERANT DISTRIBUTION NETWORK EQUIVALENT SUPPLY LENGTH (MAX):	185 ft.
COMMUNICATION / MONITORING:	MODBUS, BACNET, or SNMP
CERTIFICATION:	ISO 9001
CHILLED WATER FLOW RATE:	140 GPM
MAX SUPPLY PRESSURE:	100 psig
RPW CHILLED WATER DELTA AT FULL LOAD:	12°F
CHILLED WATER SUPPLY TEMP:	45°F
WATER CONNECTION SIZE:	2.5 in. NOM (2.625 in. ODF)
ALLOWABLE WATER PRESSURE DIFFERENTIAL:	15 – 75 psid

Features

-  Assembled in the USA.
-  Industry standard hardware and software for easy BMS integration.
-  Aesthetic design with flexible location and compact footprint.
-  Energy efficient redundant pump motor and VFD with automatic changeover.
-  System designed with cooling capacity management to efficiently handle load change fluctuations.
-  Intuitive 10-inch touchscreen controls.
-  Dynamic self-balancing pressure independent flow control valve for precise capacity control.



[Opticooltechnologies.com](https://www.opticooltechnologies.com)
Info@opticooltech.com

855 Publishers pkwy,
Webster, NY 14580 USA

Sales 585-347-6142
Service 585-967-5434